



Professional & Stable

FEATURES

- Electronic control
 - LED display with soft buttons
 - Rotary compressor
 - Big and stable wheels
- Big metal handle
 - Washable air filter
 - Removable water pump
 - Hot gas bypass system
- Quick water pipe connector
 - Vent hose can be connected
 - Simplified operation
 - CE approved by TUV Rheinland

TECHNICAL SPECIFICATIONS

For European Market	
Model	DY-55L
Power Supply	220-240V~ 50Hz
Dehumidifying Capacity	55L/day(30°C RH80%) 30L/day(27°C RH60%)
Power Consumption	720W
Air Volume	350m³/h
Noise Level	58dB(A)
Operating Temperature	5~35°C
Refrigerant	R410A
Net Weight	39.0 kg
Gross Weight	42.0 kg
Product Size(W × D × H)	545 × 500 × 638 mm
Packing Size(W × D × H)	605 × 540 × 700 mm
Loading Quantity 20'GP	114pcs
40'GP	246pcs
40'HQ	246pcs

Professional & Stable

FEATURES

- Electronic control
 - LED display with soft buttons
 - Rotary compressor
 - Big and stable wheels
- Big metal handle
 - Washable air filter
 - Removable water pump
 - Hot gas bypass system
- Quick water pipe connector
 - Vent hose can be connected
 - Simplified operation
 - CE approved by TUV Rheinland
ETL approved by INTERTEK

TECHNICAL SPECIFICATIONS

For European Market		For American Market
Model	DY-65L	DY-65L
Power Supply	220-240V~ 50Hz	115V~ 60Hz
Dehumidifying Capacity	65L/day(30°C RH80%) 38L/day(27°C RH60%)	137pints/day (86°F 80%RH) 76pints/day (80°F 60%RH)
Power Consumption	760W	7.3amps
Air Volume	400m³/h	235CFM
Noise Level	58dB(A)	58dB(A)
Operating Temperature	5~35°C	33~100°F
Refrigerant	R410A	R410A
Net Weight	36.5 kg	81.0 lbs.
Gross Weight	39.5 kg	91.0 lbs.
Product Size(W × D × H)	510 × 485 × 810 mm	20 × 19 × 32 in.
Packing Size(W × D × H)	560 × 540 × 860 mm	22 × 21 × 34 in.
Loading Quantity 20'GP	80pcs	80pcs
40'GP	176pcs	176pcs
40'HQ	260pcs	260pcs