

CEILING DEHUMIDIFIER

DY-C200DZB/DY-C240DZB



► TECHNICAL SPECIFICATIONS

| Model | DY-C200DZB | DY-C240DZB |
|--------------------------|--|--|
| Power supply | 380V 3N~50Hz | 380V 3N~50Hz |
| Dehumidifying capacity | 200L/day(30°C RH80%) 115L/day(27°C RH60%) | 240L/day(30°C RH80%) 145L/day(27°C RH60%) |
| Rated power | 2484W | 2550W |
| Rated current | 5.6A | 6.0A |
| Max power | 3360W | 3650W |
| Max current | 7.2A | 7.1A |
| Air flow(Low Fan Speed) | / | / |
| Air flow(High Fan Speed) | 1400m ³ /h | 1700m ³ /h |
| Noise level | 58dB(A) | 60dB(A) |
| Refrigerant | R410A/1.45kg | R410A/1.9kg |
| Operating Temperature | 5~35°C | 5~35°C |
| Net weight | 123 kg | 140 kg |
| Product size(W*D*H) | 1137 × 900 × 510 mm | 1137 × 900 × 540 mm |

CEILING DEHUMIDIFIER

DY-C400DZB/DY-C480DZB



► TECHNICAL SPECIFICATIONS

| Model | DY-C400DZB | DY-C480DZB |
|--------------------------|--|--|
| Power supply | 380V 3N~50Hz | 380V 3N~50Hz |
| Dehumidifying capacity | 400L/day(30°C RH80%) 240L/day(27°C RH60%) | 480L/day(30°C RH80%) 260L/day(27°C RH60%) |
| Rated power | 4600W | 5000W |
| Rated current | 10.2A | 11.5A |
| Max power | 6250W | 7700W |
| Max current | 12.5A | 15.5A |
| Air flow(Low Fan Speed) | / | / |
| Air flow(High Fan Speed) | 3000m ³ /h | 3350m ³ /h |
| Noise level | 62dB(A) | 69dB(A) |
| Refrigerant | R410A/1.9*2kg | R410A/1.9*2kg |
| Operating Temperature | 5~35°C | 5~35°C |
| Net weight | 210 kg | 220 kg |
| Product size(W*D*H) | 1280 × 1200 × 605 mm | 1270 × 1200 × 605 mm |