



Specifications

Model	DYD-Y10A	DYD-Y12A	DYD-Y16A
Power Supply	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying capacity	10L/day(30°C RH80%) 6L/day(27°C RH60%)	12L/day(30°C RH80%) 7.5L/day(27°C RH60%)	16L/day(30°C RH80%) 9.5L/day(27°C RH60%)
Power	175W	175W	225W
Air Volume	-High 95m ³ /h -Low 80m ³ /h	95m ³ /h 80m ³ /h	110m ³ /h 90m ³ /h
Noise Level	-High 39dB(A) -Low 36dB(A)	39dB(A) 36dB(A)	40dB(A) 38dB(A)
Water Tank	2.2L	2.2L	2.2L
Operating Temperature	5~35°C	5~35°C	5~35°C
Refrigerant	R290	R290	R290
Net Weight	10.0 kg	10.1 kg	10.6 kg
Gross Weight	11.0 kg	11.1 kg	11.6 kg
Product Size (W × D × H)	299 × 210 × 468 mm	299 × 210 × 468 mm	299 × 210 × 468 mm
Packing Size (W × D × H)	360 × 270 × 530 mm	360 × 270 × 530 mm	360 × 270 × 530 mm
Loading Quantity 20'GP	512pcs	512pcs	512pcs
	40'GP 1,056pcs	1,056pcs	1,056pcs
	40'HQ 1,320pcs	1,320pcs	1,320pcs

Model	DYD-Y20A	DYD-Y25A	DYD-Y50A
Power Supply	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying capacity	20L/day(30°C RH80%) 12L/day(27°C RH60%)	25L/day(30°C RH80%) 15L/day(27°C RH60%)	50L/day(30°C RH80%) 28L/day(27°C RH60%)
Power	250W	315W	680W
Air Volume	-High 155m ³ /h -Low 135m ³ /h	155m ³ /h 135m ³ /h	350m ³ /h 310m ³ /h
Noise Level	-High 42dB(A) -Low 40dB(A)	43dB(A) 41dB(A)	50dB(A) 47dB(A)
Water Tank	4.2L	4.2L	6.3L
Operating Temperature	5~35°C	5~35°C	5~35°C
Refrigerant	R290	R290	R290
Net Weight	12.2 kg	13.2 kg	23.5 kg
Gross Weight	14.0 kg	15.0 kg	26.0 kg
Product Size (W × D × H)	319 × 237 × 472 mm	319 × 237 × 472 mm	406 × 285 × 620 mm
Packing Size (W × D × H)	385 × 285 × 580 mm	385 × 285 × 580 mm	460 × 350 × 685 mm
Loading Quantity 20'GP	480pcs	480pcs	240pcs
	40'GP 1,008pcs	1,008pcs	510pcs
	40'HQ 1,008pcs	1,008pcs	510pcs

Features

- Air Purifying
- Clothes Drying
- Sleeping Mode
- Auto Dehumidifying
- Built - In Ionizer
- 24 Hours Timer - off
- Safety Child Lock

Accessory Selectable

- 10mm HEPA Filter
- 10mm Carbon Filter
- Drainage Pipe 30cm / 60cm / Customized

Certification Programs

GS, CE, RoHS Approved by SGS

