



Specifications

Model	DYD-Z12A	DYD-Z16A	DYD-Z22A	DYD-Z26A
Power Supply	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying Capacity	12L/day(30°C RH80%)	16L/day(30°C RH80%)	22L/day(30°C RH80%)	26L/day(30°C RH80%)
	7.5L/day(27°C RH60%)	9.5L/day(27°C RH60%)	13L/day(27°C RH60%)	16L/day(27°C RH60%)
Power	165W	215W	245W	320W
Air Volume	- High	105m³/h	155m³/h	155m³/h
	- Medium	/	145m³/h	140m³/h
	- Low	80m³/h	135m³/h	130m³/h
Noise Level	- High	40dB(A)	46dB(A)	46dB(A)
	- Medium	/	44dB(A)	44dB(A)
	- Low	35dB(A)	42dB(A)	43dB(A)
Water Tank	2.3L	4.5L	4.5L	4.5L
Operating Temperature	5~35°C	5~35°C	5~35°C	5~35°C
Refrigerant	R290	R290	R290	R290
Net Weight	10.5 kg	14.7 kg	15.3 kg	15.4 kg
Gross Weight	11.7 kg	16.7 kg	17.3 kg	17.4 kg
Product Size(W × D × H)	308 × 229 × 478 mm	360 × 242 × 548 mm	360 × 242 × 548 mm	360 × 242 × 548 mm
Packing Size(W × D × H)	360 × 280 × 520 mm	437 × 307 × 587 mm	437 × 307 × 587 mm	437 × 307 × 587 mm
Loading Quantity 20'GP	528pcs	288pcs	288pcs	288pcs
	40'GP	1,092pcs	600pcs	600pcs
	40'HQ	1,365pcs	800pcs	800pcs

What you can enjoy

- Keep your room at the most comfortable humidity as you want.
- Energy saving feature offers you another way to save money.
- Auto switch off when water tank full.
- Laundry drying function to speed up the clothes drying.

Accessory Selectable

- 12mm HEPA Filter
- 12mm Carbon Filter
- Drainage Pipe 30cm / 60cm / Customized

Certification Programs

GS, CE, CB, RoHS Approved by TUV Rheinland

