

RESIDENTIAL ESS SOLUTION

DEYE SPRING SE SERIES



Flexible

- ④ Modular design, easy to expand, Max. 64 units in parallel, Max. capacity of 327kWh
- ④ Suited to residential and commercial applications for increasing the self-consumption ratio



Safer

- ④ Cobalt Free Lithium Iron Phosphate (LFP) Battery : Safety and long Lifespan, high efficiency and high power
- ④ density intelligent BMS, providing complete protection



Convenient

- ④ Battery module auto networking, easy maintenance, support remotely monitoring and upgrade, support USB drive upgrade the firmware.



Reliable

- ④ Support high discharge power
- ④ IP20, natural cooling
- ④ Wide temperature range : -20°C to 55°C



Eco-Friendly

- ④ Use environmental protection materials, the whole module non-toxic, pollution-free

≥6000

Cycles

327kWh

Max. Capacity

70%

EOL

10 Years

Warranty



Rack-Mounted Battery (LV)

Model	SE-G5.1 Pro-B	
Main Parameter		
Battery Chemistry	LiFePO ₄	
Built-in Circuit Breaker	125A 2P, 60Vdc	
Capacity (Ah)	100	
Scalability	Max. 64 pcs pack (327kWh) in parallel (Max. 32 pcs no external setup)	
Nominal Voltage (V)	51.2	
Operating Voltage (V)	43.2 ~ 57.6	
Energy (kWh)	5.12	
Usable Energy (kWh) ^[1]	5.12	
Charge / Discharge Current (A) ^[2]	Recommend	50
	Max	100
	Peak (2mins, 25°C)	150
Other Parameter		
Recommend Depth of Discharge	100%	
Dimension (W × H × D, mm)	440 × 133 × 540	
Weight Approximate (kg)	45	
Master LED Indicator	5LED (SOC : 20% ~ SOC100%), 3LED (working, alarming, protecting)	
IP Rating of Enclosure	IP20	
Operating Temperature	Charge : 0~55°C/Discharge : -20°C~55°C	
Storage Temperature	0°C ~ 35°C	
Humidity	5% ~ 95%	
Altitude	≤2000m	
Cycle Life	≥6000 (25°C±2°C, 0.5C / 0.5C, 90%DOD, 70%EOL)	
Installation	Wall-Mounted, Floor-Mounted, Rack-Mounted (19-inch standard cabinet, cabinet depth ≥600mm)	
Communication Port	CAN2.0, RS485	
Warranty Period ^[3]	10 years	
Energy Throughput	16MWh@70%EOL	
Certification	UN38.3, IEC62619, CE, UK, VDE 2510-50, CEI 0-21, FCC, UL1973, UL9540A	

[1] DC Usable Energy, test conditions: 100% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

[2] The current is affected by temperature and SOC.

[3] Conditions apply, refer to Deye Warranty Letter.



Typical Configuration

Support 12kW, 15kW inverters to connect the battery, and 3 to 12 batteries can be connected in parallel.

1 hour solution	3xSE+12kW Inverter	3xSE+15kW Inverter
2 hours solution	5xSE+12kW Inverter	6xSE+15kW Inverter
3 hours solution	8xSE+12kW Inverter	9xSE+15kW Inverter
4 hours solution	10xSE+12kW Inverter	12xSE+15kW Inverter