



Professional & Stable

FEATURES

- Electronic control
- LED display with soft buttons
- Rotary compressor
- Big and stable wheels
- Big metal handle
- Washable air filter
- Removable water pump
- Hot gas bypass system
- Quick water pipe connector
- Vent hose can be connected
- Simplified operation
- CE approved by TUV Rheinland

TECHNICAL SPECIFICATIONS

Model		DY-55L	
Power Supply		220-240V~ 50Hz	
Dehumidifying Capacity		55L/day(30°C RH80%)	
		30L/day(27°C RH60%)	
Power Consumption		720W	
Air Volume		350m³/h	
Noise Level		58dB(A)	
Operating Temperature		5~35°C	
Refrigerant		R410A	
Net Weight		39.0 kg	
Gross Weight		42.0 kg	
Product Size(W × D × H)		545 × 500 × 638 mm	
Packing Size(W × D × H)		605 × 540 × 700 mm	
Loading Quantity 20'GP		114pcs	
40'GP		246pcs	
40'HQ		246pcs	

Professional & Stable

FEATURES

- Electronic control
- LED display with soft buttons
- Rotary compressor
- Big and stable wheels
- Big metal handle
- Washable air filter
- Removable water pump
- Hot gas bypass system
- Quick water pipe connector
- Vent hose can be connected
- Simplified operation
- CE approved by TUV Rheinland
- ETL approved by INTERTEK

TECHNICAL SPECIFICATIONS

Model		DY-65L	
Power Supply		220-240V~ 50Hz	115V~ 60Hz
Dehumidifying Capacity		65L/day(30°C RH80%)	137pints/day (86°F 80%RH)
		38L/day(27°C RH60%)	76pints/day (80°F 60%RH)
Power Consumption		760W	7.3amps
Air Volume		400m³/h	235CFM
Noise Level		58dB(A)	58dB(A)
Operating Temperature		5~35°C	33~100°F
Refrigerant		R410A	R410A
Net Weight		36.5 kg	81.0 lbs.
Gross Weight		39.5 kg	91.0 lbs.
Product Size(W × D × H)		510 × 485 × 810 mm	20 × 19 × 32 in.
Packing Size(W × D × H)		560 × 540 × 860 mm	22 × 21 × 34 in.
Loading Quantity 20'GP		80pcs	80pcs
40'GP		176pcs	176pcs
40'HQ		260pcs	260pcs