



Professional & Stable

FEATURES

- Electronic control
- LED display with soft buttons
- Rotary compressor
- Big and stable wheels
- Big metal handle
- Washable air filter
- Removable water pump
- Hot gas bypass system
- Quick water pipe connector
- Vent hose can be connected
- Simplified operation
- CE approved by TUV Rheinland
- ETL approved by INTERTEK

TECHNICAL SPECIFICATIONS

	For European Market	For American Market
Model	DY-65N	DY-80P
Power Supply	220-240V~ 50Hz	115V~ 60Hz
Dehumidifying Capacity	65L/day(30°C RH80%) 38L/day(27°C RH60%)	137pints/day (86°F 80%RH) 76pints/day (80°F 60%RH)
Power Consumption	760W	7.8amps
Air Volume	400m³/h	235CFM
Noise Level	58dB(A)	58dB(A)
Operating Temperature	5~35°C	33~100°F
Refrigerant	R410A	R410A
Net Weight	37.0 kg	87.0 lbs.
Gross Weight	40.0 kg	94.0 lbs.
Product Size(W × D × H)	572 × 498 × 815 mm	22.5 × 19.5 × 32 in.
Packing Size(W × D × H)	620 × 580 × 870 mm	24.5 × 23 × 34.5 in.
Loading Quantity 20'GP	72pcs	72pcs
40'GP	152pcs	152pcs
40'HQ	228pcs	228pcs

Professional & Stable

FEATURES

- Electronic control
- LED display with soft buttons
- Rotary compressor
- Big and stable wheels
- Big metal handle
- Washable air filter
- Removable water pump
- Hot gas bypass system
- Quick water pipe connector
- Vent hose can be connected
- Simplified operation
- CE approved by TUV Rheinland
- ETL approved by INTERTEK

TECHNICAL SPECIFICATIONS

	For European Market	For American Market
Model	DY-85L	DY-85L
Power Supply	220-240V~ 50Hz	115V~ 60Hz
Dehumidifying Capacity	85L/day(30°C RH80%) 50L/day(27°C RH60%)	180pints/day (86°F 80%RH) 105pints/day (80°F 60%RH)
Power Consumption	990W	7.5amps
Air Volume	700m³/h	410CFM
Noise Level	58dB(A)	58dB(A)
Operating Temperature	5~35°C	33~100°F
Refrigerant	R410A	R410A
Net Weight	45.0 kg	97.0 lbs.
Gross Weight	49.0 kg	108.0 lbs.
Product Size(W × D × H)	530 × 515 × 830 mm	21 × 20 × 32.5 in.
Packing Size(W × D × H)	610 × 580 × 870 mm	24 × 23 × 34.5 in.
Loading Quantity 20'GP	72pcs	72pcs
40'GP	152pcs	152pcs
40'HQ	228pcs	228pcs