

CEILING DEHUMIDIFIER

DY-C200DZB/DY-C240DZB



► TECHNICAL SPECIFICATIONS

Model	DY-C200DZB	DY-C240DZB
Power supply	380V 3N~50Hz	380V 3N~50Hz
Dehumidifying capacity	200L/day(30°C RH80%) 115L/day(27°C RH60%)	240L/day(30°C RH80%) 145L/day(27°C RH60%)
Rated power	2484W	2550W
Rated current	5.6A	6.0A
Max power	3360W	3650W
Max current	7.2A	7.1A
Air flow(Low Fan Speed)	/	/
Air flow(High Fan Speed)	1400m³/h	1700m³/h
Noise level	58dB(A)	60dB(A)
Refrigerant	R410A/1.45kg	R410A/1.9kg
Operating Temperature	5~35°C	5~35°C
Net weight	123 kg	140 kg
Product size(W*D*H)	1137 × 900 × 510 mm	1137 × 900 × 540 mm

CEILING DEHUMIDIFIER

DY-C400DZB/DY-C480DZB



► TECHNICAL SPECIFICATIONS

Model	DY-C400DZB	DY-C480DZB
Power supply	380V 3N~50Hz	380V 3N~50Hz
Dehumidifying capacity	400L/day(30°C RH80%) 240L/day(27°C RH60%)	480L/day(30°C RH80%) 260L/day(27°C RH60%)
Rated power	4600W	5000W
Rated current	10.2A	11.5A
Max power	6250W	7700W
Max current	12.5A	15.5A
Air flow(Low Fan Speed)	/	/
Air flow(High Fan Speed)	3000m³/h	3350m³/h
Noise level	62dB(A)	69dB(A)
Refrigerant	R410A/1.9*2kg	R410A/1.9*2kg
Operating Temperature	5~35°C	5~35°C
Net weight	210 kg	220 kg
Product size(W*D*H)	1280 × 1200 × 605 mm	1270 × 1200 × 605 mm