



Features

- Air Purifying
- Clothes Drying
- Sleeping Mode
- Auto Dehumidifying
- Built - In Ionizer
- 24 Hours Timer - off
- Safety Child Lock

Accessory Selectable

- 10mm HEPA Filter
- 10mm Carbon Filter
- Drainage Pipe 30cm / 60cm / Customized

Certification Programs

GS, CE, RoHS Approved by SGS



Specifications

Model		DYD-Y10A	DYD-Y12A	DYD-Y16A
Power Supply		220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying capacity		10L/day(30°C RH80%)	12L/day(30°C RH80%)	16L/day(30°C RH80%)
		6L/day(27°C RH60%)	7.5L/day(27°C RH60%)	9.5L/day(27°C RH60%)
Power		175W	175W	225W
Air Volume	-High	95m³/h	95m³/h	110m³/h
	-Low	80m³/h	80m³/h	90m³/h
Noise Level	-High	39dB(A)	39dB(A)	40dB(A)
	-Low	36dB(A)	36dB(A)	38dB(A)
Water Tank		2.2L	2.2L	2.2L
Operating Temperature		5~35°C	5~35°C	5~35°C
Refrigerant		R290	R290	R290
Net Weight		10.0 kg	10.1 kg	10.6 kg
Gross Weight		11.0 kg	11.1 kg	11.6 kg
Product Size (W × D × H)		299 × 210 × 468 mm	299 × 210 × 468 mm	299 × 210 × 468 mm
Packing Size (W × D × H)		360 × 270 × 530 mm	360 × 270 × 530 mm	360 × 270 × 530 mm
Loading Quantity 20'GP		512pcs	512pcs	512pcs
	40'GP	1,056pcs	1,056pcs	1,056pcs
	40'HQ	1,320pcs	1,320pcs	1,320pcs

Model		DYD-Y20A	DYD-Y25A	DYD-Y50A
Power Supply		220-240V~ 50Hz	220-240V~ 50Hz	220-240V~ 50Hz
Dehumidifying capacity		20L/day(30°C RH80%)	25L/day(30°C RH80%)	50L/day(30°C RH80%)
		12L/day(27°C RH60%)	15L/day(27°C RH60%)	28L/day(27°C RH60%)
Power		250W	315W	680W
Air Volume	-High	155m³/h	155m³/h	350m³/h
	-Low	135m³/h	135m³/h	310m³/h
Noise Level	-High	42dB(A)	43dB(A)	50dB(A)
	-Low	40dB(A)	41dB(A)	47dB(A)
Water Tank		4.2L	4.2L	6.3L
Operating Temperature		5~35°C	5~35°C	5~35°C
Refrigerant		R290	R290	R290
Net Weight		12.2 kg	13.2 kg	23.5 kg
Gross Weight		14.0 kg	15.0 kg	26.0 kg
Product Size (W × D × H)		319 × 237 × 472 mm	319 × 237 × 472 mm	406 × 285 × 620 mm
Packing Size (W × D × H)		385 × 285 × 580 mm	385 × 285 × 580 mm	460 × 350 × 685 mm
Loading Quantity 20'GP		480pcs	480pcs	240pcs
	40'GP	1,008pcs	1,008pcs	510pcs
	40'HQ	1,008pcs	1,008pcs	510pcs